



HAL
open science

Air Traffic Complexity Map Based on Linear Dynamical Systems

Daniel Delahaye, Adrián García, Julien Lavandier, Supatcha Chaimatanan,
Manuel Soler

► **To cite this version:**

Daniel Delahaye, Adrián García, Julien Lavandier, Supatcha Chaimatanan, Manuel Soler. Air Traffic Complexity Map Based on Linear Dynamical Systems. Aerospace, 2022, 10.3390/aerospace9050230 . hal-03647918

HAL Id: hal-03647918

<https://enac.hal.science/hal-03647918>

Submitted on 21 Apr 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Air Traffic Complexity Map Based on Linear Dynamical Systems

Daniel Delahaye ¹, Adrián García ¹, Julien Lavandier ¹, Supatcha Chaimatanan ¹ and Manuel Soler ²,

¹ OPTIM Team, French Civil Aviation University, Toulouse France; firstname.lastname@enac.fr

² Department of Bioengineering and Aerospace Engineering UC3M, Madrid, Spain; masolera@ing.uc3m.es

* Correspondence: delahaye@recherche.enac.fr

† Current address: 7 Avenue Edouard Belin 31055 Toulouse

‡ These authors contributed equally to this work.

Abstract: This paper presents a new air traffic complexity metric based on linear dynamical systems, of which the goal is to quantify the intrinsic complexity of a set of aircraft trajectories. Previous works have shown that the structure and organization of air traffic are essential factors in the perception of the complexity of an air traffic situation. Usually they were not able to explicitly address trajectory pattern organization. The new metric, by identifying the organization properties of trajectories in a traffic pattern, captures some of the key factors involved in ATC complexity. The key idea of this work is to find a linear dynamical system which fits a vector field as closely as possible to the observations given by the aircraft positions and speeds. This approach produces an aggregate complexity metric that enables to identify high (low) complexity regions of airspace and compare their relative complexity. The metric is very appropriate to compare different traffic situations for any scale (sector or country) by associating a complexity index to each trajectory sample in the airspace. For instance, to compute the complexity for a sector, one must just sum-up complexity for trajectory samples intersecting such a sector. This computation can also be extended in the time dimension in order to estimate the average complexity in a given airspace for a period of time.

Keywords: Complexity; Dynamical System; Air Traffic Disorder

1. Introduction

Regarding air traffic management research, there have been three main objectives of interest: reduce air flight delay, solve air traffic conflicts efficiently and mitigate air space congestion. This work proposes a method to assess the latter.

The operational capacity of a control sector is measured by the maximum number of flights that may cross the sector in a given period. This measurement does not consider the direction of the traffic, treating geometrically structured and disordered traffic in the same way. Thus, in certain situations, a controller may continue to accept traffic even if operational capacity has been reached (structured traffic situation). In other cases, a controller may need to refuse airplanes even though the operational capacity has not been reached (disordered traffic situation). Thus, modeling airspace congestion using the number of airplanes per unit of time is insufficient to reflect the levels of difficulty involved in a traffic situation.

Air traffic control organizes air flows to ensure flight safety and increase the route network's capacity. In 2019, before COVID, about 8500 flights were registered everyday over France, which is a crossroad for the whole European airspace. This traffic generates a huge amount of control workload, and the airspace is then divided into elementary sectors which air navigation controllers manage. For several years, a constant increase in air traffic has induced more and more congestion in the control sectors. Two strategies can then be applied to reduce such congestion. The first one consists of adapting the demand to the existing capacity (slot-route allocation, collaborative decision-making, etc...). The second one adapts the capacity to the demand (modification of the air network, new design of the sectorization, new airports, etc...). For the two preceding approaches, the capacity of a

Citation: Delahaye, D.; García, A.; Lavandier, J.; Chaimatanan, S.; Soler, M. Title. *Aerospace* **2022**, *1*, 0. <https://doi.org/>

Received:

Accepted:

Published:

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Copyright: © 2022 by the authors. Submitted to *Aerospace* for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

sector is measured by the number of aircraft flying across the sector during a given period of time.

This study aims to synthesize a traffic complexity indicator to quantify better the congestion in the air sector, which will be more relevant than a simple number of aircraft independent of the traffic configuration. More precisely, our objective is to build a metric of the intrinsic complexity of the traffic distribution in the airspace, which relates to controller workload. Such metrics must capture the level of disorder (or organization) of any traffic distribution. Usually, metrics are focused on the speed vector distribution, and the associated disorder metric captures only some features of the traffic complexity. The real objective of our work is to build a metric that measures the disorder or organization of trajectories in 4D space (3D for space and 1D for time).

Such complexity metrics are relevant for many applications in the air traffic management area. For instance, when a sectorization is designed[1], the sectors have to be balanced from the congestion point of view and nowadays, only the number of aircraft is used to reach this objective. Another example where a congestion metric is needed is the traffic assignment[2,3] for which an optimal time of departure and a route are searched for each aircraft in order to reduce the congestion in the airspace. Complexity metric may also be used to design new air networks, for dynamic sectoring concepts, define future ATM concepts (Free Flight), etc... Complexity metrics enable to qualify and quantify the performance of the Air Traffic service providers and enable a more objective consultation between airlines and providers.

The work presented in this paper is based on dynamical systems modeling of air traffic. A dynamical system describes the evolution of a given state vector. If such a vector is given by the position of aircraft $\vec{X} = [x, y, z]^T$, a dynamical system associates a speed vector $\vec{X} = [v_x, v_y, v_z]^T$ to each point in the airspace. The key idea is to find a dynamical system that models the observed aircraft trajectories. A trajectory disorder metric can be computed based on this dynamical system modeling. The metric is targeted to measure the intrinsic traffic complexity related to a set of 4D trajectories related to the control workload. Such control workload encompasses other factors (airspace structure, etc...) that are not considered in the metric computation.

In the first part, this paper will summarize the previous related works. The second part will present a linear dynamical system modeling for which the complexity metric can be represented into a complex coordinate system. It is very easy to identify any speed vector organization pattern in this system. The third part illustrates the computation of such a metric in several traffic situations.

2. Previous Related Works

The airspace complexity is related to the traffic structure and the airspace geometry. Different efforts are underway to measure the whole complexity of the airspace.

Wyndemere Inc. [4] proposed a measure of the perceived complexity of an air traffic situation. This measure is related to the controller's cognitive workload with or without knowing the aircraft's intents. The metric is human-oriented and is then very subjective.

Laudeman et al. from NASA [5] have developed a metric called "Dynamic Density" which is more quantitative than the previous ones and is based on the flow characteristics of the airspace. The "Dynamic Density" is a weighted sum of the traffic density (number of aircraft), the number of heading changes (>15 degrees), the number of speed changes (>0.02 Mach), the number of altitude changes (>750 ft), the number of aircraft with 3D Euclidean distance between 0 – 25 nautical miles, the number of conflicts predicted in 25 – 40 nautical miles. The parameters of the sums have been adjusted by showing different traffic situations to several controllers. B. Sridhar from NASA[6] has developed a model to predict the evolution of such a metric in the near future. Efforts to define "Dynamic Density" have identified the importance of many potential complexity factors, including structural considerations.

Airspace complexity depends on both structural and flow characteristics of the airspace[6]. The structural characteristics are fixed for a sector and depend on the spatial and physical attributes of the sector, such as terrain, number of airways, airway crossings, and navigation aids. The flow characteristics vary as a function of time and depend on the number of aircraft, the mix of aircraft, weather, the separation between aircraft, etc... A combination of these structural and flow parameters influences the controller workload.

The traffic itself is not enough to describe the complexity associated with an airspace. A few previous studies have attempted to include structural consideration in complexity metrics but have done so only to a restricted degree. For example, the Wyndemere Corporation proposed a metric that included a term based on the relationship between aircraft headings and dominant geometric axis in a sector [4]. The importance of including structural consideration has been explicitly identified in recent work at Eurocontrol. In a study to identify complexity factors using judgment analysis, "Airspace Design" was identified as the second most crucial factor behind traffic volume[7]. The impact of the structure on the controller workload can be found on the paper[8,9]. Those papers show how strong the traffic structure (airways, sectors, etc...) is related to the control workload through several traffic factors dependent on the instantaneous distribution of traffic (clustering, number of aircraft, distance between aircraft, relative speed between aircraft, etc...)

The previous models do not take into account the intrinsic traffic disorder, which is related to the complexity. The first efforts related to disorder can be found in[10]. This paper introduces metrics based on geometrical properties that measure a traffic pattern's disorder. Those metrics can extract features on the traffic complexity such as proximity (measures the level of aggregation of aircraft in the airspace), convergence (for close aircraft, this metric measures how strongly aircraft are closer to each other), and sensitivity (this metric measures how the relative distance between aircraft is sensible to the control maneuver). G. Aigoïn has extended and refined the geometrical class by using a cluster-based analysis[11]. Two aircraft are said to be in the same cluster if the product of their relative speed and their proximity (a function of the inverse of the relative distance) is above a threshold. For each cluster, a metric of relative dependence between aircraft is computed, and the whole complexity of the cluster is then given by a weighted sum of the matrix norm. Those norms give an aggregated measure of the level of proximity of aircraft in clusters and the associated convergence. From the cluster matrix, it is also possible to compute the difficulty of a cluster (it measures how hard it is to solve a cluster). Multiple clusters can exist within a sector, and their interactions must also be considered. A measure of this interaction has been proposed by G. Aigoïn [11]. This technique allows multiple complexity metrics to be developed, such as average complexity, maximum and minimum cluster complexities, and complexity speeds.

Another approach based on fractal dimension has been proposed by S. Mondoloni and D. Liang in[12]. Fractal dimension is a metric comparing traffic configurations resulting from various operational concepts. It allows, in particular, to separate the complexity due to sectorization from the complexity due to traffic flow features. The dimension of geometrical figures is well-known: a line is of dimension 1, a rectangle of dimension 2, etc. The application of this concept to air route analysis consists in computing the fractal dimension of the geometrical figure composed of existing air routes. Fractal dimension provides information on the number of degrees of freedom used in the airspace: a higher fractal dimension indicates more degrees of freedom. Therefore, the fractal dimension measures the geometrical complexity of a traffic pattern.

Some new geometrical metrics have been developed in[13] which are able to capture the level of disorder or the level of organization for some traffic patterns. For instance, in an artificial roundabout moving, the speed vectors are very different even if the global moving is fully organized without any changes in the relative distance between aircraft. The covariance and the Koenig metrics have been developed to capture those features. The first one is able to identify the disorder or organization of translation movements. The second one identifies organized curl moving.

In[10] another approach based on nonlinear dynamical system modeling of the air traffic uses the topological entropy as a measure of the disorder of the traffic pattern. This approach represents more faithfully the traffic's structure but requires a lot of computation for establishing the metric. First, the non-linear dynamical system is adjusted to the observations in order to build the associated vector field. Then, Lyapunov exponents are computed in order to characterize the overall properties of the vector field. When an exponent has a high value, it shows a high sensitivity to initial conditions meaning the situation is difficult to predict. In this case the traffic situation presents a high level of disorder. Unfortunately, this metric is not able to take uncertainties into account which is the case when one want to predict congestion in the near future.

We propose in this paper an approximation of such a metric based on the linear dynamical system, which measures the local disorder of a set of trajectories in the neighborhood of a given aircraft at a given time. This approximation is much faster to compute and can take into account uncertainties of the future position of aircraft, which is not possible with the nonlinear dynamical system framework described in[10].

3. Metric Description (Linear Dynamical System Modeling)

The investigated indicator will be linked to the air traffic modeling by a linear dynamical system, yielding an intrinsic measure of complexity of the geometry of the traffic. This enables to identify different structures of organization of the aircraft speed vectors such as translation, curve organizations, divergence, convergence, or a mix of them.

3.1. Model

The key idea of this metric is to model the set of aircraft trajectories by a linear dynamical system. A dynamical system models a vector field by a set of differential equations which describes and controls the evolution of a given state vector and is defined by the following equation:

$$\dot{\vec{X}} = \mathbf{A} \cdot \vec{X} + \vec{B} \quad (1)$$

\vec{X} is the state vector of the system:

$$\vec{X} = \begin{bmatrix} x \\ y \end{bmatrix} \quad (2)$$

In this equation, we only consider the observations' x and y components since air traffic controllers see two dimensions speed vectors on their screens. Moreover, the metric will be computed for each flight level in a given airspace. Equation 1 associates a speed vector $\dot{\vec{X}}$ with each point in the state space \vec{X} . This synthesis is a particular vector field. The average behavior of this vector field is given by the vector \vec{B} and the linear mapping between the speed vector $\dot{\vec{X}}$ and the position vector \vec{X} is given by matrix \mathbf{A} . Therefore, the coefficients of matrix \mathbf{A} and vector \vec{B} determine the mode of evolution of the system in relation to its dynamics.

More precisely, the eigenvalues of this matrix will determine the behavior of the system and will be used to obtain the complexity metric. The properties and relevance of these eigenvalues will be explained in section 3.3.

First, we focus on defining and modeling the linear dynamical system that will allow us to obtain matrix \mathbf{A} . Our problem therefore consists on determining the dynamical model which is closest to the observations: Those observation are extracted from the radar trackers (positions and speeds of aircraft at a given time). We then consider that for each aircraft, we have set position \vec{X}_i and speed measures \vec{V}_i at some consecutive time stamps i :

$$\vec{X}_i = \begin{bmatrix} x_i \\ y_i \end{bmatrix}$$

$$\vec{V}_i = \begin{bmatrix} v_{x_i} \\ v_{y_i} \end{bmatrix}$$

An example of such observations is given on figure 1 for which aircraft observation 187
are represented by the blue arrows.




Figure 1. Radar captures associated with three aircraft. In this example only one time sample is 188
considered. 189

We thus wish to find the vector field described by a linear equation $(\dot{\vec{X}} = \mathbf{A} \cdot \vec{X} + \vec{B})$ 189
which is best fitted to our observations. To illustrate this aspect, we construct a grid over the 190
airspace (see Figure 2) on which we carry out a regression of a vector field that minimizes 191
the error between the model and the observations. In order to use matrix forms, we rewrite 192
equation 1 as $\mathbf{V} = \mathbf{C} \cdot \mathbf{X}$, introducing the following matrices: 193

$$\mathbf{X} = \begin{bmatrix} x_1 & x_2 & x_3 & \cdots & x_n \\ y_1 & y_2 & y_3 & \cdots & y_n \\ 1 & 1 & 1 & \cdots & 1 \end{bmatrix} \quad (3)$$

$$\mathbf{V} = \begin{bmatrix} v_{x_1} & v_{x_2} & v_{x_3} & \cdots & v_{x_n} \\ v_{y_1} & v_{y_2} & v_{y_3} & \cdots & v_{y_n} \end{bmatrix} \quad (4)$$

$$\mathbf{C} = \left[\underbrace{\begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix}}_{\mathbf{A}} \mid \underbrace{\begin{bmatrix} b_1 \\ b_2 \end{bmatrix}}_{\vec{B}} \right] \quad (5)$$

where $\mathbf{X} \in \mathbb{R}^{3 \times n}$, $\mathbf{V} \in \mathbb{R}^{2 \times n}$, $\mathbf{C} \in \mathbb{R}^{2 \times 3}$, $\mathbf{A} \in \mathbb{R}^{2 \times 2}$, $\vec{B} \in \mathbb{R}^{2 \times 1}$ and n represents the 194
number of observations at a given instant (number of aircraft present in a sector at a given 195
instant). 196
197
198




Figure 2. Vector field produced by the linear dynamic system

3.2. Regression

The dynamical system has to be adjusted with the minimum error based on the aircraft observations (positions and speed vectors). This fitting has been done with a Least Mean Square minimization (LMS) method[14]. For each considered aircraft i , it is supposed that position $\vec{X}_i = [x_i, y_i]^T$ and speed vector $\vec{V}_i = [v_{x_i}, v_{y_i}]^T$ are given. We then construct an error criterion E , between the dynamical system model and the observation, based on a norm (Euclidean, in our case), which should be minimized in relation to matrix \mathbf{A} and vector \vec{B} , and therefore in relation to matrix \mathbf{C} , which represents the parameters of the model:

$$\begin{aligned}
 E &= \sqrt{\sum_{i=0}^{i=n} \|\vec{V}_i - (\mathbf{A} \cdot \vec{X}_i + \vec{B})\|^2} \\
 &= \sqrt{\sum_{i=0}^{i=n} \|\vec{V}_i - (\mathbf{C} \cdot \vec{X}_i)\|^2} \tag{6}
 \end{aligned}$$

In a matrix form:

$$E = \|\mathbf{V} - \mathbf{C} \cdot \mathbf{X}\|$$

E minimization is the same as E^2 minimization: $E^2 = \|\mathbf{V} - \mathbf{C} \cdot \mathbf{X}\|^2$.
The derivative of such expression with respect to \mathbf{C} is given by:

$$\nabla_{\mathbf{C}} E^2 = -2 \cdot (\mathbf{V} - \mathbf{C} \cdot \mathbf{X}) \cdot \mathbf{X}^T$$

E is minimum when: $\nabla_{\mathbf{C}} E = 0 \Rightarrow \mathbf{C} \cdot \mathbf{X} \cdot \mathbf{X}^T = \mathbf{V} \cdot \mathbf{X}^T$ then:

$$\mathbf{C}_{opt} = \mathbf{V} \cdot \mathbf{X}^T \cdot (\mathbf{X} \cdot \mathbf{X}^T)^{-1}$$

On the right side, we recognize the pseudo-inverse of matrix \mathbf{X}^T :

$$\mathbf{X}^+ = \mathbf{X}^T \cdot (\mathbf{X} \cdot \mathbf{X}^T)^{-1}$$

In some situations, $\mathbf{X} \cdot \mathbf{X}^T$ is not invertible, and the computation of the \mathbf{C}_{opt} is not possible by using such equation. In this case, the classical Singular Value Decomposition (SVD) trick is applied:

$$\mathbf{X}^T \cdot (\mathbf{X} \cdot \mathbf{X}^T)^{-1} = \mathbf{L}^T \cdot \mathbf{S}^{-1} \cdot \mathbf{R}$$

where \mathbf{S} is a diagonal matrix containing the singular values (only the significant singular values are inverted in this formula in order to control the conditioning of the algorithm).

$$\Rightarrow \mathbf{C}_{opt} = \mathbf{V} \cdot \mathbf{L}^T \cdot \mathbf{S}^{-1} \cdot \mathbf{R}$$

Based on \mathbf{C} the matrix \mathbf{A} is extracted for which an eigenvalue decomposition is computed:

$$\mathbf{A} = \mathbf{U} \cdot \mathbf{D} \cdot \mathbf{U}^T$$

The diagonal matrix \mathbf{D} contains the eigenvalues. When such eigenvalues have positive real parts, the system is in expansion mode, and when they are negative, the system is in contraction mode.

In addition the vector \vec{B} represents the global tendency of the vector field.

3.3. Properties of Eigenvalues

The eigenvalues of matrix \mathbf{A} describe and summarize the evolution of the system. These eigenvalues are complex numbers. Their real parts are related to the convergence or the divergence property of the system in the direction of the eigenvector. When such eigenvalues have positive real parts, the system is in expansion mode (produces divergence), and when they are negative, the system is in contraction mode (produces convergence). The absolute value of these real parts is proportional to the level of contraction or expansion of the system: the larger those real parts are in absolute value, the faster the evolution. Furthermore, the imaginary part of the eigenvalues is related to the level of rotation tendency of the system: the tendency of the system to organize itself following a global rotation movement associated with each of the eigen axes. Depending on those eigenvalues, a dynamical system can evolve in contraction, expansion, rotation, or a combination of those three modes.

We will refer to a fully organized traffic pattern when the relative distances between aircraft do not change with time. For such a situation, the traffic is very predictable and very comfortable to address by a controller: trajectories do not present any difficulties. These patterns are translation, rotation, or both.

Then, the evolution properties of the system related to the position of the eigenvalues can be summarized in the complex coordinate system (see Figure 3). In this coordinate system, it is then possible to identify the locus of the eigenvalues of matrix \mathbf{A} associated with organized traffic situations: the vertical strip around the imaginary axis. Therefore, organized situations are located around the imaginary axis: when the relative distances between aircraft change slowly with time (this means that the relative speeds between aircraft are close to zero and the traffic has no interaction).




Figure 3. Impact of the eigenvalues of matrix A on the dynamics of the system

As an example (see Figure 4), the eigenvalues of matrix A have been calculated for a situation with three aircraft located on a circumference, for which only the orientation of the speed vectors is modified in order to create four traffic situations (pure translation, convergence, divergence, and pure rotation). As we can see in Figure 4, the pure translation and pure rotation are the two organized traffic situations since they have eigenvalues in the central band of the complex plane.




Figure 4. Eigenvalues loci for 4 traffic situations

In the first case, the eigenvalues $\vec{\lambda}$ are null because the aircraft are flying in parallel, representing a translation: distances between aircraft remain unchanged with time. In the second case, the eigenvalues are real negative; the system evolves in a contraction mode, and the four aircraft are converging: the norms of the relative distances between aircraft diminish with time. The third situation represents an expansion evolution for which the eigenvalues are real positive, and the aircraft are diverging: the relative distances increase with time. In the two previous situations, the distance between aircraft changes with time, not being organized traffic patterns. The last situation is associated with full imaginary eigenvalues for which the aircraft stay at the same distance from each other in a

curl moving. The computation of matrices \mathbf{A} , vectors \vec{B} , and $\vec{\lambda}$ is given for these previous examples: 261
262

Translation	Convergence	Divergence	Rotation
$\mathbf{A} = \begin{bmatrix} 0 & 0 \\ 0 & 0 \end{bmatrix}$	$\mathbf{A} = \frac{v}{d} \cdot \begin{bmatrix} -1 & 0 \\ 0 & -1 \end{bmatrix}$	$\mathbf{A} = \frac{v}{d} \cdot \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$	$\mathbf{A} = \frac{v}{d} \cdot \begin{bmatrix} 0 & 1 \\ -1 & 0 \end{bmatrix}$
$\vec{B} = \begin{bmatrix} v \\ 0 \end{bmatrix}$	$\vec{B} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$	$\vec{B} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$	$\vec{B} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$
$\vec{\lambda} = \frac{v}{d} \cdot \begin{bmatrix} 0 \\ 0 \end{bmatrix}$	$\vec{\lambda} = \frac{v}{d} \cdot \begin{bmatrix} -1 \\ -1 \end{bmatrix}$	$\vec{\lambda} = \frac{v}{d} \cdot \begin{bmatrix} +1 \\ +1 \end{bmatrix}$	$\vec{\lambda} = \frac{v}{d} \cdot \begin{bmatrix} +j \\ -j \end{bmatrix}$

(7)

Looking at Figure 4, the small squares are the initial positions of aircraft at a given time (this represents the observation given by radar, for instance, with the associated speed vector). As it can be seen, the aircraft are initially located on a circumference with a diameter of $2 \cdot d$. The positions of aircraft two and three are symmetric to the x-axis. All the speed norms are the same and have been fixed at v . The vector field associated with each one of these four situations is shown in Figure 5. 263
264
265
266
267
268




Figure 5. Vector field produced for the 4 toy examples. The red arrows represent the vector field of the associated linear dynamical system model.

3.4. Extension with uncertainties

If we want to predict complexity in a given airspace, one must be able to take into account future aircraft positions uncertainties which are crossing such airspace. Those uncertainties are linked to the wind and temperature encountered by the aircraft along its route. So, future positions of aircraft will be represented by a segment along its trajectory arc length in the future. Therefore, since we should account for these uncertainties, it has been considered that at every sample time of the analysis, each aircraft that is within the current modeled airspace area can be ahead or behind its actual position. Then, a time shift is applied to each aircraft (i.e., the reference one and the neighbors) to account for ten forward and ten backward positions. Each shift is equal to twelve seconds, so the most forward and backward positions are separated two minutes with respect to the reference position.

In order to simplify the following figures, we will consider only two shifts in each direction (five positions in total per aircraft) instead of ten only for the visualization of the uncertainties problem in this current section. In Figure 6, the three aircraft from Figure 1 are expanded with their corresponding forward and backward positions after applying a time-shifting.




Figure 6. Uncertainties associated with three aircraft

Figure 7 shows the vector field produced by the linear dynamical system corresponding to the above situation.




Figure 7. Vector field of the uncertainties extension

Figure 8 compares the vector field of the situation with and without the uncertainties extension. 288
289




Figure 8. Traffic situation with and without uncertainties

This extension will make matrix X larger since from here on, n would be equal to 290
 $5 \cdot \text{number of aircraft}$. 291

3.5. Metric computation 292

The problem will be analyzed within a certain airspace region (e.g., France FIR), so 293
only the aircraft that are within its boundary are analyzed. By assessing this problem in 294
discrete-time along one aircraft trajectory and considering an area of influence surrounding 295
this aircraft to account for other aircraft, this metric represents the local disorder that is 296
present in the vicinity of an aircraft along its trajectory at each time. 297

Having obtained matrix A and its eigenvalues, the metric is built by summing the 298
negative real part of such eigenvalues λ hereinafter. 299

Therefore, the procedure that we apply consists of solving the *LMS* method while 300
following an aircraft along all the position observations of its trajectory. This aircraft will be 301
referred to as the reference aircraft. As for the aircraft that are flying in its vicinity, they will 302
be referred to as neighbor aircraft. Every aircraft within the searching area of the reference 303
aircraft at each time will be considered as a neighbor aircraft, and therefore, its observations 304
will be used in the *LMS* computation (at each time, the neighbor aircraft may be different). 305
This searching area is defined as a box window (24.8×24.8 NM) centered at each reference 306
aircraft position. This dimension is based on the longitudinal separation minima applicable 307
to en-route aircraft multiplied by a scalar factor. 308

The uncertainty extension will be applied to both reference and neighbor aircraft. So 309
matrix A is computed using the observations of the reference and neighbor aircraft and 310
their uncertainties as well, at each time. Figure 9 shows the geometry of the problem that is 311
solved for a reference aircraft at a given time. 312




Figure 9. Example of local trajectory interaction at a given time

3.6. Neighborhood definition

In order to reflect operational features, the metric has been extended to the third dimension by using three-dimensional state space. From the operational point of view, what is relevant for air traffic controllers is the horizontal speed of the aircraft and their climbing/descending rate. So, the model has been extended in this direction by considering only some aircraft in the neighborhood of a given aircraft.

When the reference aircraft is climbing or descending, all the other aircraft in the neighborhood will be considered as neighbors. For a cruising reference aircraft, one must apply filtering to account for aircraft that are flying in the same flight level; however, an extension of this filter was necessary to account for the aircraft that were changing their altitude and then were likely to interact with other aircraft since they would be flying at the same altitude at some point of the analysis period. The criteria applied to both the reference and neighbor aircraft to filter the possible aircraft affecting the local disorder can be seen in Figure 10.




Figure 10. Aircraft altitude evolution that has an interaction with a certain FL

When the neighbor aircraft altitude (after applying the searching area principle) is close to the reference aircraft altitude, that neighbor aircraft is considered as an actual neighbor aircraft. In RVSM (Reduced Vertical Separation Minima) airspace, en-route aircraft vertical separation is 1000 ft between FL290 and FL410. The filter is set to look for neighbor aircraft within a vertical separation, with respect to the reference one, equal to 3000 ft. Therefore, aircraft flying within 30 flight levels above and below the reference aircraft will be considered for the metric. The filter allows the following situations for both the reference and neighbor aircraft: (a) aircraft is climbing to the reference aircraft altitude, (b) aircraft is descending to reference aircraft altitude, (c) aircraft is about to climb from

reference aircraft altitude, (d) aircraft is about to descend from reference aircraft altitude, (e) aircraft is climbing and will fly from a lower to a higher altitude than reference aircraft altitude, (f) aircraft is at reference aircraft altitude, (g) aircraft is descending and will fly from a higher to a lower altitude than reference aircraft altitude.

When two cruising aircraft are flying at different altitudes (see the example given in Figure 11), such aircraft will never be considered as neighbors because they will always stay separated thanks to the vertical separation.




Figure 11. Lack of interdependency between two consecutive flight level trajectories

After filtering the neighboring aircraft associated with a reference aircraft (at a given time t), the LMS computation is applied in order to identify the \mathbf{A} matrix. The metric is then computed based on the eigenvalues of such \mathbf{A} matrix and assigned to the reference aircraft at time t . This computation is done for each trajectory sample along the route.

Having this complexity metric computed along the trajectory, it is possible to establish a color map that shows the aircraft involved in congested areas.

4. Results

4.1. Toy Examples

Different traffic samples have been created in order to compare the complexity metric previously described. For the following toy examples, no uncertainties are considered and every aircraft is flying at the same flight level. Six traffic situations will be classed according to an increasing level of difficulty (increasing order of complexity) as a function of predictability and interdependency between trajectories. The full trajectories of aircraft are shown in the following figures, where a green circle symbolizes their initial positions. Figure 12 shows a parallel flow of aircraft. It represents an easy situation since aircraft relative distances keep the same and in this case this is no complexity (null \mathbf{A} matrix; see equation 7).






Figure 12. Parallel flow

Figure 13(a) shows a full symmetric convergence of eight aircraft flying at the same speed. It represents an average situation with high sensitivity and conflicts with no interaction between solutions. In order to build an aggregated metric along the time dimension, we compute for each time sample the associated eigenvalues of the \mathbf{A} matrix for which the real parts are summed up in order to produce a scalar value (Figure 13(b)). It must be noticed that the metric begins to be negative, showing the situation is globally

converging. If we continue evaluating that situation along time, after the crossing of the aircraft, the metric becomes positive, and the situation is globally diverging. 366
367




(a) Eight aircraft converging at the same point.




(b) Evolution of the real part of \mathbf{A} matrix eigenvalues.

Figure 13. Scalar metric function of time for eight aircraft converging at the same point. As it is shown there is a discontinuity when aircraft cross each other but if we consider more aircraft in the crossing, the curve will be scaled accordingly (more aircraft will induce larger negative and positive values).

Figure 14(a) shows a fuzzy convergence of aircraft in the same area. Aircraft do not necessarily have the same speed. 368
369



(a) Random aircraft converging in the same area.



(b) Scalar metric for random aircraft converging in the same area.

Figure 14. Complexity evolution with time associated to the fuzzy convergence situation.

In this case, the metric first identifies a soft converging pattern. Then, it reaches a minimum in the central area of convergence (matching the maximum convergence tendency) and begins to be positive, meaning that the aircraft are diverging at that moment (see Figure 14(b)) and then reaches its maximum (matching the maximum divergence tendency). 370
371
372
373
374

We then consider two flow crossing situations. The first situation has a crossing angle of 30 degrees (see Figure 15), and the second one has a crossing angle of 90 degrees (see Figure 16). The right side of both figures represents the evolution of the complexity metric with time. As expected, the metric starts to be negative as the aircraft start first to converge and become positive (divergence) after the crossing point. The shapes of the curve are the 375
376
377
378
379

same. Only the magnitude is higher with the 90 deg situation, which is expected since the relative speed between aircraft is higher in this situation.




Figure 15. N-S and W-E flows crossing at 30 deg. Traffic situation on the left, complexity function of time on the right.




Figure 16. N-S and W-E flows crossing at 90 deg. Traffic situation on the left, complexity function of time on the right.

It is worth mentioning that in these three cases. However, each aircraft possesses a different speed. The eigenvalues are always real: the no-curl tendency is perceived since the set of aircraft is flying only along two different trajectory directions.

4.2. Real Airspace

This complexity metric has been computed on traffic simulated with real flight plans of aircraft crossing the French airspace (as a matter of fact, using real traffic data like radar tracking records is meaningless because such traffic has been managed by the controller and complexity has been removed). Based on such flight plans, an arithmetic simulator based on the BADA database has been used in order to create 8000 four-dimensional trajectories in the french airspace. The trajectory has then been sampled every 20 seconds, representing two million 4D points for the whole day. The metric has been computed for each trajectory and for each time step in a 4D cube (three spatial dimensions and one time dimension) and projected on a two-dimensional coordinate system to have a complexity map as shown in Figure 17. On this figure, the metric has been normalized between 0 (blue color) and 100% (maximum with red color). As expected, the highest complexity is located near the

big crossings. One must remember that the map represents the accumulated complexity in altitude and time. A 2D point at (x,y) on the map represents all 4D points at those 2D coordinates (x,y) .

The metric has been implemented in Java. Thanks to some algorithmic improvements, the computation time needed to compute the metric for the whole day of traffic (two million points) is less than ten milliseconds on a core i7 Laptop computer.




Figure 17. Traffic complexity of a traffic sample over French airspace. For each 4D point (x,y,z,t) of each trajectory, the complexity metric is computed and represented with a color map on a two dimension map (x,y) .

5. Conclusion

This paper has introduced an efficient traffic complexity metric that can identify the level of disorder of a given traffic situation. A Linear Dynamical System model is first regressed based on a least mean square approach based on a set of trajectory samples. An SVD trick has been used in order to avoid conditioning issues in the LMS process. Then, the eigenvalues of the associated \mathbf{A} matrix of the linear dynamical system are extracted to quantify the disorder of the traffic situation (sum of the negative real parts). When such a metric has to be computed for a predicted traffic situation, one must be able to take into account uncertainties. This uncertainty has been taken into account by considering aircraft as segments in the time dimension in order to produce a robust metric. This metric has been successfully tested on several artificial traffic situations and on a full day of traffic over the french airspace. Based on the high performance for computing this metric (for a large number of trajectories), the next step consists of using this metric in an optimization algorithm to minimize congestion in a given airspace, which is one of the objectives of the START SESAR project.

Author Contributions: Conceptualization, D.D, A.G, S.C and M.S; methodology, D.D, A.G, J.L, S.C and M.S; software, D.D, A.G and J.L; validation, D.D, A.G, J.L, S.C and M.S

Funding: The SESAR START project has founded the research (grant number 893204).

Conflicts of Interest: The authors declare no conflict of interest.

Sample Availability: Samples of the compounds ... are available from the authors.

Abbreviations

The following abbreviations are used in this manuscript:

ATC	Air Traffic Control	423
ATM	Air Traffic Management	424
BADA	Base of Aircraft Data	
COVID	COrona VIRus Disease	
FIR	Flight Information Region	
LMS	Least Mean Square	
NASA	National Aeronautics and Space Administration	425
NM	Nautical Mile	
RVSM	Reduced Vertical Separation Minima	
SESAR	Single European Sky's ATM Research	
START	Stable and resilient ATM by integrAting Robust airline operations into the neTwork	
SVD	Singular Value Decomposition	

References

1. Sergeeva, M.; Delahaye, D.; Mancel, C.; Vidosavljevic, A. Dynamic airspace configuration by genetic algorithm. *Journal of Traffic and Transportation Engineering* **2017**, *4*, 300 – 314. doi:10.1016/j.jtte.2017.05.002. 427
2. Oussedik, S.; Delahaye, D. Reduction of air traffic congestion by genetic algorithms. *Lecture Notes in Computer Science* **1998**, *1498*, pp 855–864. doi:10.1007/BFb0056927. 428
3. Alam, S.; Chaimatanan, S.; Delahaye, D.; Féron, E. A Meta-Heuristic Approach for Distributed Trajectory Planning for European Functional Airspace Blocks. *Journal of Air Transportation* **2018**, *26*, 81–93. doi:10.2514/1.D0078. 429
4. Wyndemere. *An evaluation of air traffic control complexity*. Technical report, NASA 2-14284, 1996. 430
5. Laudeman, I.; Shelden, S.; Branstrom, R.; Brasil, C. *Dynamic density : an air traffic management metric*. Technical report, NASA/TM-1998-112226, 1998. 431
6. Sridhar, B.; Sheth, K.; Grabbe, S. *Airspace complexity and its application in air traffic management*. Proceedings of the 2nd USA/Europe Air Traffic Management R&D Seminar. Eurocontrol/FAA, 1998, 1998. 432
7. Kirwan, B.; Scaife, R.; Kennedy, R. *Investigating complexity factors in UK Air Traffic Management*. *Human Factors and Aerospace Safety* **1(2)** **2001**. 433
8. Histon, J.; Hansman, R.; Aigoïn, G.; Delahaye, D.; Puechmorel, S. *Introducing structural consideration into complexity metrics*. Proceedings of the 4th USA/Europe Air Traffic Management R&D Seminar. Eurocontrol/FAA, 2001, 2001. 434
9. Histon, J.; Hansman, R.; Gottlieb, B.; Kleinwaks, H.; Yenson, S.; Delahaye, D.; Puechmorel, S. *Structural consideration and cognitive complexity in air traffic control*. Proceedings of the 21st Air Traffic Management for Commercial and Military Systems. IEEE, AIAA, 2002, 2002. 435
10. Delahaye, D.; Puechmorel, S. *Air traffic complexity : Towards intrinsic metrics*. Proceedings of the 3rd USA/Europe Air Traffic Management R&D Seminar. Eurocontrol/FAA, 2000, 2000. 436
11. Aigoïn, G. *Air traffic complexity modeling*. Master's thesis, Ecole Nationale de l'Aviation Civile, 2001. 437
12. Mondoloni, S.; Liang, D. *Airspace fractal dimension and applications*. Proceedings of the 4th USA/Europe Air Traffic Management R&D Seminar. Eurocontrol/FAA, 2001, 2001. 438
13. Delahaye, D.; Paimblanc, P.; Puechmorel, S.; Histon, J.; Hansman, R. *A new air traffic complexity metric based on dynamical system modelization*. Proceedings of the 21st Air Traffic Management for Commercial and Military Systems. IEEE, AIAA, 2002, 2002. 439
14. Björck, Å. *Numerical methods for least squares problems*. *Society for Industrial & Applied Mathematics* **1996**. 440